

NM12-135

12V135Ah / 10hr rate**BATTERY**
Genergy

Introduction

Genergy NM (33Ah-250Ah) series is designed for standby use with 10-year design life in float service. The series battery is featured of high consistency, excellent performance and reliable standby service life. It is widely applied in float service, UPS/EPS, medical equipment, telecom, photovoltaic, control system and security system.

Battery Features

- Absorbent Glass Mat (AGM) Technology for efficient gas recombination of up to 99% maintenance free and fixed orifice plate pasting technology
- Low self-discharge
- Fully tank formed plates
- Low impurity electrolyte
- Flame retardant ABS casing with UL94-V0 is available upon request.
- Very high purity lead

Electrical Specification

Design floating Life @ 25°C (77°F)	10 years
Nominal Capacity @ 25°C /77°F	
20 hour rate 7.16A to 1.75Vpc	143.2 Ah
10 hour rate 13.96A to 1.75Vpc	139.6 Ah

Internal Resistance

(Fully charged battery @ 25°C /77°F) 4.5mΩ

Max. Discharge Current @ 25°C /77°F 1350 A (5S)

Charge Methods: Constant voltage charge @ 25°C /77°F

Cycle Use 14.7 ~ 14.9V

Max. Current 33 A

Standby Use 13.6 - 13.8V

Operating Temperature Range -30 ~ 50°C


Notes: battery voltage must be adjusted according to temperature.

Please refer to our recommendation.

Self-Discharge

3% of capacity declined per month @ 25°C (77°F).

Battery Picture & Terminal Layout



Dimension & Weight

Length	Dimension (± 2mm)			Total Height	Weight (± 2%)
	Width	Height			
342 mm	172 mm	283 mm	288 mm		41.5 kg
13.5 inch	6.8 inch	11.1 inch	11.3 inch		91.5 lbs

Typical Applications

- Telecommunications
- Power Utility
- Data Center
- UPS & EPS

Certificates



Constant Current Discharge (Amperes @ 25°C /77°F)

V/cell	10min	15min	20min	25min	30min	35min	40min	45min	50min	55min	1hr	2hr	3hr	4hr	5hr	10hr	20hr
1.60	284.12	216.89	187.36	157.84	133.60	132.43	123.49	115.32	107.83	101.34	102.21	55.42	39.43	32.75	26.77	14.31	7.23
1.65	269.80	205.95	178.88	151.81	130.02	128.93	120.43	112.68	105.63	99.58	100.83	54.34	38.68	32.06	26.16	14.24	7.23
1.70	258.65	197.45	171.82	146.19	125.84	124.66	116.49	109.05	102.34	96.63	98.05	52.51	37.78	31.31	25.54	14.10	7.23
1.75	246.72	188.33	164.15	139.97	121.07	119.95	112.34	105.42	99.27	94.11	95.97	51.06	36.96	30.62	24.99	13.96	7.16
1.80	233.98	178.61	156.08	133.54	116.29	115.13	107.96	101.47	95.76	91.05	93.19	49.22	36.07	29.86	24.37	13.60	7.09

Constant Power Discharge (Watts/cell @ 25°C /77°F)

V/cell	10min	15min	20min	25min	30min	35min	40min	45min	50min	55min	1hr	2hr	3hr	4hr	5hr	10hr	20hr
1.60	493.43	376.66	331.48	286.30	249.57	248.02	230.39	214.18	199.11	186.39	186.35	102.44	74.55	61.86	50.94	28.54	15.06
1.65	475.92	363.30	320.38	277.47	243.00	241.45	224.48	208.90	194.50	182.45	182.88	100.36	73.86	61.17	50.25	28.27	15.06
1.70	457.62	349.33	308.48	267.64	235.25	233.78	217.70	202.97	189.45	178.29	179.41	97.94	72.49	60.11	49.50	27.72	14.86
1.75	437.72	334.14	295.57	257.01	226.89	225.46	210.27	196.37	183.75	173.47	175.25	94.83	70.43	58.63	48.61	27.51	14.59
1.80	416.23	317.74	281.65	245.57	217.94	216.49	202.17	189.12	177.39	168.00	170.39	91.47	68.57	57.15	47.51	27.24	14.45


Subject to revision without notice. Please contact our sales representatives for latest version.

Web: www.genergybattery.com | Email: sales@genergybattery.com

NM12-135

12V135Ah / 10hr rate**BATTERY**
Genenergy

Graphs



Subject to revision without notice. Please contact our sales representatives for latest version.

Web: www.genenergybattery.com | Email: sales@genenergybattery.com